



Our poly lifting process uses a 2-part, high density foam, which is injected beneath the sunken slab through a series of small holes.

Our material does not lose it's density, is lightweight and hydrophobic in nature, which makes this structural grade polyurethane an attractive option for specific projects.

#### HOURS OF OPERATION

Day	Hours
Monday	9:00am - 5:00pm
Tuesday	9:00am - 5:00pm
Wednesday	9:00am - 5:00pm
Thursday	9:00am - 5:00pm
Friday	9:00am - 5:00pm
Saturday	Closed
Sunday	Closed

## Poly Lifting & Leveling

Your cost effective alternative to concrete replacement

Richard Farist  
Owner



**Concrete Corrections**

Concrete Lifting & Leveling \* Void Fill \* Soil Stabilization


Servicing GA, SC, FL

Office 770-558-5862

richard@correctyourconcrete.com  
www.correctyourconcrete.com

**770-558-5862**

Call Us Today!



**Concrete Corrections**

www.correctyourconcrete.com  
info@correctyourconcrete.com

**Concrete Corrections**

www.correctyourconcrete.com



## About Us

At Concrete Corrections, we understand the importance of eliminating property owners' liability exposures by raising and stabilizing settled or sunken concrete.

Our goal is to offer a Cost Effective repair solution, utilizing polyurethane foam, for concrete lifting and leveling, which then will void fill and stabilizes settled or unsupported concrete back to original position.

Our objective is to minimize your downtime while ensuring a long term solution for your concrete slab.

We are determined to create a customer experience worthy of referral.



**Concrete Corrections**

[www.correctyourconcrete.com](http://www.correctyourconcrete.com)



We repair problem  
**Sidewalks** **Driveways** **Void Fills**  
**Pool Decking** **Sunken -**  
**Steps** **Patios** etc.

**FREE**  
**ESTIMATES**

## Polyurethane Foam Facts

### Incredible Strength

- Supports approximately 7,200 lbs / cu ft
- Works in wet environments
- Bonds with soil and concrete
- High density, will not resettle

### Lightweight Material

- Our foam weighs approximately 4 lbs / cu ft
- Considered a "closed cell" foam
- Perfect for compromised soil
- Edges are neatly trimmed

### Quick Results

- Initial reaction time is 10 seconds
- 90% cured within 15 minutes
- Injected as a hot liquid, cures instantly
- Most projects are complete in 1 day

## What Is Polyurethane Foam Used For?

- |                     |                        |
|---------------------|------------------------|
| Settled Front Steps | Sunken Pool Decking    |
| Crooked Walkway     | Void Fill Eroded Areas |
| Uneven Patio        | Driveway Apron Support |
| Dipped Garage Floor | Warehouse Flooring     |
| Settled Home        | Poorly Compacted Areas |
| Seawall Repair      | Bulkhead Stabilization |

## Our Services

- Poly Lifting and Leveling
- Void Fill and Support
- Soil Stabilization
- Deep Injection
- Erosion Control
- Helical Pier Systems